AP	PLIC	ATI	ON 7	#																						
Pro	pert	y Ov	vner:	•																Dat	e:					
	Ade													Mai	Mailing Address :											
										, M	0															
	odivi													Day)					ning)	-		
									Location: 1/4			·				,T		,R								
Residence - # Bedrooms: # People							Latitud						Longitude:													
Business - Type:				Design flow:				gpd; S		System is:		: N	ew 🗆	Replacement		Repair □										
			1		1							T														
																							4	India		
																								No	rtn	
																									-	
																						-				
												SITE	DIA	GRAI	M											
			LEG	END																						
								L				L	L						L			_				
																CPO	SS SECT	TON								

<u>Site Diagram and Cross-Section:</u> Show relative location of buildings, wells, roads, rock outcrops, depressions, sinkholes, location of soil observations, etc. Indicate the evaluated area(s) and direction of slope. (Property lines, easements, buried utilities, etc., are as observed, or as reported by property owner)

SOIL PROFILE DESCRIPTION

Owner:										Date:					
SOIL CHAP	RACTERIS	TICS				Excavat	tion Dep	th:		Pit (required	d for new	installa	tion) o	r Core #:	
Vegetation	:					Parent I	Material:								
Suitability	Horizon		Munsell	Redoximorphic	Text	ıre	% Co Fragn		Consis		Roots	Sh /S/	Gr S	Applica	tion Rate
(S, PS, U)	Designation Depth / Boundary		Color (moist)	Features (2)	USDA	% Clay	by vol	ume >3"	-tence	Structure	/Pores	Shrink /Swell	Soil Group	Conv. (Table 13)	LPP (Table 14)

Notes:			

Notations used on Soil Profile Description

Boundary distinctness: A-abrupt, C-clear, G-gradual; topography: S-smooth, W-wavy, I-irregular;

Redox Features Report low chroma Munsell colors and iron and manganese concentrations indicative of soil drainage limitations;

Texture s-sand, Is-loamy sand, sl-sandy loam, I-loam, sil-silt loam, si-silt, scl-sandy clay loam, cl-clay loam, sicl-silty clay loam, sc-sandy clay, sic-silty clay, c-clay; Designate estimated clay content for all horizons;

Consistence (report moist consistence) moist: fr-friable, fi-firm, vfi-very firm; wet: ss-slightly sticky, s-sticky, vs-very sticky and sp-slightly plastic, p-plastic, vp-very plastic; dry: sh-slightly hard, h-hard, vh-very hard;

Structure grade: 1-weak, 2-moderate, 3-strong; size: f-fine (thin if platy), m-medium, c-coarse (thick if platy); shape: ABK-angular blocky, SBK-subangular blocky, GR-granular, PL- platy, PR prismatic, MA-massive;

Roots/Pores abundance: f-few, c-common, m-many; size: vf-very fine, f-fine, m-medium, c-coarse.



GREENE COUNTY RESOURCE MANAGEMENT DEPARTMENT ENVIRONMENTAL

SITE EVALUATION for ONSITE WASTEWATER TREATMENT SYSTEM

SITE CLASSIFICATION for ONSITE SEWAGE SYSTEM – 19 CSR 20-3.060(2) & (7)

Owner:		Pit/Co	ore #: Da	te:						
<u>Suitability</u>	See recommendations below S – Suitable; PS – Provisio	nally Suitable; U –	Unsuitable; for con	ventional system.						
	LANDSCAPE POSITION:		Slope aspe	ct:						
_	Flooding frequency: None \square Rare \square Occasional \square Frequency	ent □ Surfac	Surface depression(s) in evaluated area?							
	& TOPOGRAPHY Percent Slope:	Slope Type: Uniform□ Complex □								
	Shape across (contour):	Shape down (pro	ofile):							
_	SOIL CHARACTERISTICS (See Profile Description for deta	ails)								
	TEXTURE to a depth ofinches	Depth of unsuitable	le texture	inches						
	STRUCTURE to a depth of inches	Depth of unsuitab	le structure	inches						
	SOIL DRAINAGE Type of water table:		Depth to water tak	leinches						
	Surface drainage limitations:		Runoff slope lengt	h feet						
	SOIL THICKNESS Depth of bedrock:	inches	Rock outcrops? _							
	RESTRICTIVE HORIZON Type:	[Depth: 7	hickness:						
	AVAILABLE SPACE Estimated space available:_									
	Adequate for a conventional system? An alternative	native system?	Replacer	ment area?						
_	OTHER FACTORS Note any environmental hazards:									
-	High groundwater contamination potential? (If yes, indicate reason):									
	Sinkhole ☐ Rapid permeability ☐ Depth to highly perm	neable bedrock 🗆	Fill material/dept	h 🗆						
	OVERALL Notes:									
	Overall site classification will be determined by the low	est of the uncorrec	table characteristic	<u> </u>						
• S Ar	overall site classification of suitable indicates soil and site of									
	ntional absorption system.		alamaian danima a							
	es classified as provisionally suitable require some modific tion for a conventional system or alternative system to function		pianning, design, a	na						
 U Sit (7)(K). 	tes originally classified as unsuitable may possibly be reclas	sified as provisio r	nally suitable acco	rding to subsection						
. , . ,	suitable site may be used for soil absorption systems, provid	ed engineering, hy	drogeologic and so	il studies						
indicate	e to the administrative authority that a conventional or alternactorily. These sites may be reclassified as provisionally suit	tive system could	be expected to fund	tion						
	strative authority according to subsection (6)(K).	able apon meeting	, the requirements t	or the						
Recommer	Recommendations* associated with Provisionally Suitable or Unsuitable classifications:									
Trenches must not be dug when wet to prevent damaging soil/trench surfaces.										
	Surface water diversion is needed.									
	An interceptor drain should be installed upslope at a d		inches.							
	Shallow or modified shallow placed trenches should b			inches.						
	An alternative/engineered system is needed to overco	ine site ilmitations.								
				_						

Owner:		Date	:
Comments/Recommendations:			
*Recommendations are to assist the property the administrative authority.	owner and their agents in	complying with the standards, a	nd are subject to approval by
I, the undersigned, hereby certify that the si 701.059 RSMo and 19 CSR 20-3.060 and			
Print name	OSE ID#	Signature	Date

Important Recommendations for Installers and Homeowners:

Protect the absorption area before and after construction. Do not drive over or store excavated materials on field area etc.

Shallow placed absorption systems utilize more permeable and better-aerated soil horizons.

Do not install soil absorption system when soil is wet. Redirect surface water, house guttering, and foundation drains away from absorption field.

Establish & maintain adequate vegetative cover over the field. Regularly inspect, maintain, and pump your sewage system.

Install water saving devices & practice water conservation. Check for and repair any water leaks as soon as discovered.

Spread out water use, such as laundry, throughout the week.

Restrict garbage disposal use.

Do not put fats or grease into the sewage system. Keep chemicals and hazardous wastes out of your system.

Use disinfectants and high strength cleaners sparingly.

Do not plan any building improvements, patios, etc. near the sewage system or repair area.

Minimum Set-Back Distances

Based on Table 1 of Greene County Regulations and Standards for On-Site Wastewater Systems

Minimum Distance From	Sewage Tank (1)	Disposal Area (2)	Lagoons
Private water supply well	(Feet) 50	(Feet) 100	(Feet) 100
Public water supply well (Community or Non-Community)	300	300	300
Classified stream, lake or impoundment*	50	50	50
Cistern	50	50	50
Faults, photo lineaments, or fracture trends (5)	100	100	100
Ground source heat pump well	50	100	100
Spring	200	200	200
Stream or open ditch	25	25	25
Property line	10	10**	75
Building foundation	5	15	see section 6(D)
Basement	15	25	see section 6(D)
Deck	5	15	see section 6(D)
Other soil absorption systems except repair areas	1	20	20
Sinkhole rim (4)	100	100	100
Suction water line	50	100	100
Swimming Pool	25	25	25
Top of slope of embankments or cuts of two feet (2') or more vertical height	_	20	20
Upslope interceptor drains	-	10	10
Water line under pressure	10	10	10
Electric or other utility lines	5	5	5

See pages 3-8 and 3-9 for setbacks and footnotes to Table 1